



## CRACKकोFILL

Revision: 01/10/2020

Page 1 of 2

### Technical Data:

Consistency	Paste
Curing System	Physical drying
Skin formation (20°C/65% R.H.)	Approx. 20 min.
Shrinkage (DIN 52451)	Approx. 15%
Specific Gravity (DIN 53479B)	1.72g/ml
Temperature Resistance	-20°C to +80°C
Maximum allowed Distortion	Ca 16%

\* This varies according to ambient conditions such as temperature, humidity, substrate etc.

### Product:

CrackकोFill is premium quality physical curing high grade acrylic based paintable sealant.

### Characteristics:

- Best for interior & exterior purpose
- Maximum gap filling capacity 6-7mm
- Easy to use
- No sag
- Non toxic
- Paintable
- Non flammable

### Applications:

- Joints with movements up to 16%
- Connection joints in the building industry
- Fill cracks on plaster wall, between door/window frames & wall joints

### Packaging:

Colour: white

Packaging: 425g cart & 1kg pack

### Shelf life and storage:

12 months from date of manufacturing in unopened packaging stored in a cool and dry place at recommended temperatures between +5°C and +25°. Protect against frost

### Surfaces:

Type: all porous building surfaces

State of Surface: clean, dry, free of dust and grease

Preparation: prepare very porous surfaces with diluted CrackकोFill (1 part CrackकोFill & 2 parts water)

We recommend a preliminary compatibility test

### Joint Size:

Minimum Width: 5mm

Maximum Width: 20mm

Minimum Depth: 5mm

Recommendation: joint depth = joint width

Use PE backer rods in case of large joint dimensions to avoid three-sided adhesion

### Applying the sealant:

Method: Apply the sealant by means of a saptula. Smoothen the sealant with a filling-knife. Use sand paper to sand dry surface for smooth finishing.

Application temperature: +5°C to +30°C, do not apply when rain or frost are imminent

Clean: Uncured CrackकोFill can be removed from tools with water. Cured sealant must be removed mechanically

Finishing: with water

Repair: with CrackकोFill

**Remark:** The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

**McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.**

Unit No. 505 B, Tower B, 5th Floor, BPTP Park Centra, Sector-30, NH-8, Gurugram, Haryana - 122002 (India)

Phone No.: 8010-114-114 | www.mccoysoudal.com | Email: info@mccoysoudal.com



---

## **CRACKकोFILL**

---

**Revision: 01/10/2020**

**Page 2 of 2**

**Health- and safety recommendations:**

Apply the usual industrial hygiene  
Consult the label for more information

**Remarks:**

- Do not use in applications where continuous water immersion is possible
- Do not apply when rain or frost is imminent
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended
- CrackकोFill can be painted over with most paints

**Remark:** The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

---

**McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.**

Unit No. 505 B, Tower B, 5th Floor, BPTP Park Centra, Sector-30, NH-8, Gurugram, Haryana - 122002 (India)

Phone No.: 8010-114-114 | [www.mccoysoudal.com](http://www.mccoysoudal.com) | Email: [info@mccoysoudal.com](mailto:info@mccoysoudal.com)