



ACRYRUB PRO+

Revision: 01/02/2016

Page 1 of 2

Technical Data:

Consistency	Paste
Curing System	Physical drying
Skin formation (20°C/65% R.H.)	Approx. 20 min.
Shrinkage (DIN 52451)	Approx. 15%
Specific Gravity (DIN 53479B)	1,70g/ml
Temperature Resistance	-20°C to +80°C
Maximum allowed Distortion	15%

* This varies according to ambient conditions such as temperature, humidity, substrate etc.

Product:

Acryrub Pro+ is a high-quality, plasto-elastic one-component joint sealant based on acrylic dispersions.

Characteristics:

- Very easy to apply
- Colourfast and waterproof after curing
- Can be painted over after curing
- Very good adhesion on many porous surfaces and aluminium

Applications:

- Joints with movements up to 15%
- Connection joints in the building industry
- Joints between windowsills, between skirting-board and floor, between brickwork, etc

Packaging:

Colour: white,
Packaging: cartridge 450g

Shelf life and storage:

12 months from date of manufacturing in unopened packaging stored in a cool and dry place at recommended temperatures between +5°C and +25°. Protect against frost

Surfaces:

Type: all porous building surfaces
State of Surface: clean, dry, free of dust and grease
Preparation: prepare very porous surfaces with diluted Acryrub Pro+ (1 part Acryrub Pro+ & 2 parts water)
We recommend a preliminary compatibility test

Joint Size:

Minimum Width: 5mm
Maximum Width: 20mm
Minimum Depth: 5mm
Recommandation: joint depth = joint width

Use PE backer rods in case of large joint dimensions to avoid three-sided adhesion

Applying the sealant:

Method: Apply the sealant by means of a handheld or pneumatic caulking gun. Smoothen the sealant with a filling-knife
Application temperature: +5°C to +30°C, do not apply when rain or frost are imminent
Clean: Uncured Acryrub Pro+ can be removed from tools with water. Cured sealant must be removed mechanically
Finishing: with water
Repair: with Gap Filler

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)



ACRYRUB PRO+

Revision: 01/02/2016

Page 2 of 2

Health- and safety recommendations:

Apply the usual industrial hygiene
Consult the label for more information

Remarks:

- Do not use in applications where continuous water immersion is possible
- Do not apply when rain or frost is imminent
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended
- Acryrub Pro+ can be painted over with most paints

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)