



WINDOWSEAL

Revision: 01/01/2018

Page 1 of 2

Technical Data:

Consistency	Paste
Curing System	Moisture Cure
Skin formation (20°C/65% R.H.)	Ca 20-30 min.
Shrinkage (DIN 52451)	≤ 15%
Specific Gravity (DIN 53479B)	1.45g/mL
Temperature Resistance	-20°C to +80°C
Maximum gap filling capacity	8mm
Movement capability	± 20%

Product:

Windowseal is suitable for interior and exterior sealing applications of all kinds of door and window joints and connection joints for aluminium, uPVC & wood.

Shelf life and storage:

12 month from date of manufacturing in unopened packaging stored in a cool and dry place at recommended temperatures between +5°C and +35°. Protect against frost.

Characteristics:

- For window & door professionals (uPVC, aluminium & wood)
- Ideal for Indian weather conditions
- Maximum gap filling capacity 8mm
- Movement capability ± 20%
- Good UV resistance

Not suitable for:

- Natural stone
- Structural glazing
- Mirrors
- Glass to glass
- Automotive applications

Applications:

- Telecom Shelters, uPVC Profiles, aluminium fenestration, door & window frames, ACP glass, brick, concrete, wood
- Building and construction joints
- Topsealing between treated wood and glass and between uPVC and glass or aluminium and glass
- Sealing between uPVC and glass

Joint Size:

Maximum gap filling capacity: 8mm

Applying the sealant:

Method: Apply the sealant by means of a handheld or pneumatic caulking gun. Smoothen the sealant with a filling-knife

Application temperature: +5°C to +35°C, do not apply when rain or frost are imminent

Clean: Uncured Windowseal can be removed from tools with water. Cured sealant must be removed mechanically

Packaging:

Colour: white

Packaging: cartridge 270ml

Finishing: with water

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)



WINDOWSEAL

Revision: 01/01/2018

Page 2 of 2

Health- and safety recommendations:

Apply the usual industrial hygiene
Consult the label for more information

Remarks:

- Do not use in applications with continuous water immersion
- Do not apply when rain or frost is imminent
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended
- Windowseal can be painted over with most paints

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

McCoy Soudal Sealants Adhesives & Foams Pvt. Ltd.

McCoy Corporate Tower, C-55, Okhla Industrial Area, Phase-1, New Delhi - 110020 (INDIA)

Tel.: +91 11 40623344 (100 lines) | Fax: +91 11 40623355

Website: www.mccoysoudal.com | Email: info@mccoysoudal.com

1800-121-6569 (Toll Free)